

PRODUCT DESCRIPTION: ANTISLIP (AG) is selected special silica BROADCASTING aggregate with Graded and factory blended.

AREAS OF APPLICATION

For making textured, non-skid surface of epoxy, pu, waterproofing, etc:

- Car parking, Ramps
- Chemical Plants
- Pharmaceutical Industries
- Food Processing Areas
- Bottling Plants
- Electric/Electronics Industries
- Hospital
- Nuclear Power Plants
- Dairies & Breweries
- Multi-level Car park area
- Aerospace Industry, Airport Hangers
- Fermentation
- Terrace waterproofing

ADVANTAGE

- Graded give same textured surface
- anti-skid property
- Inert so not alter the product properties
- Give slip resistance floor property
- Suitable with wide range of products
- Easy application

APPLICATION

SURFACE PREPARATION

Epoxy, pu or other surface must be tacky for proper adhesion.

MIXING

No need to mix.

APPLICATION

Sprinkle the aggregate over tacky surface of base coat. After dry remove excess amount by brush.

TECHNICAL SPECIFICATIONS

Physical appearance	Granular and natural color
Coverage	2-2.5 kg/m ² depends on surface condition

PACKAGING

Pack size 25kg bag cover 10m²@2.5kg/m².

STORAGE

Store the material at temperatures between + 10° C and + 45° C in originally sealed packages, the material can be stored for 24 months.

NOTE

The information supplied in this datasheet is based upon extensive experience and is given in good faith in order to help you. Our company policy is one of continuous Research and Development; we therefore reserve the right to update this information at any time without prior notice. We also guarantee the consistent high quality of our products however as we have no control over site conditions or the execution of the work, we accept no liability for any loss or damage which may arise as a result thereof.

HEALTH AND SAFETY

This material is intended to be used by trained professionals with proper equipment's. The following safety measures are recommended:

- Wear protective gloves, clothing, goggles, hearing protection for noise reduction and hard hats for falling debris.
- Do not eat, drink or smoke while in active contact with these materials.
- Avoid skin contact.
- Wash hands thoroughly with soap and cool water.
- Never wash the skin with a solvent.
- Anyone experiencing difficulty breathing when working with these materials or showing an allergic reaction should seek fresh air immediately and consult a physician if symptoms persist.

DISCLAIMER:

Fibrex Construction Chemicals pvt. Ltd. products though are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale, copies of which may be obtained on request. Fibrex wishes to clarify that any advice, recommendation, specification or information is accurate and correct, though it cannot, at any time assume any liability either directly or indirectly arising from the use of its products. This is because it has no direct or constant control over where or how its products are applied, and whether or not in accordance with the advice specification, recommendation or information given by it.

FIBREX OTHER PRODUCTS – WE DO

